



Technical Data // FRI2.5

Push-In Type | Initiator clamp

4 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions


Stripped length	12.0 mm
Width	5.1 mm
Height	47.0 mm
Length	72.0 mm
Height TS35 x 7.5	48.0 mm

ELECTRICAL DATA

General

Cross connection channels	3
---------------------------	---

COLOURS

	BEIGE, similar RAL 1019
---	-------------------------

**Technical Data // FRI2.5**

Push-In Type | Initiator clamp

4 Connections

CONNECTION DIAGRAM

Bitte kontaktieren Sie unsere Vertriebsmitarbeiter.
Please contact our sales department.

ORDER DATA

Article Designation	Article Number	PU
FRI2.5-BEIGE	43295.2	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate SIT6.3x32-10A-32V	4917430.2	20
Cross-Connection insulated FQI2.5/2	493462.8	50
Cross-Connection insulated FQI2.5/3	493463.8	50
Cross-Connection insulated FQI2.5/4	493464.8	20
Cross-Connection insulated FQI2.5/5	493465.8	20
Cross-Connection insulated FQI2.5/6	493466.8	20
Cross-Connection insulated FQI2.5/7	493467.8	20
Cross-Connection insulated FQI2.5/8	493468.8	10
Cross-Connection insulated FQI2.5/9	493469.8	10
Cross-Connection insulated FQI2.5/10	493460.8	10
Cross-Connection insulated FQI2.5/50	493461.8	5
End Stopn ZES35/2	493811.2	50
Labelling Adapters FBA1	493424.2	50
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	300 V	300 V	250 V
Rated current	10 A	10 A	24 A
Rated wire size	AWG 26-12	AWG 26-12	2.5 mm ²
Rated impulse voltage			4 kV
Pollution degree			3